

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 1 of 10

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: **HIPOL SEMISYNTHETIC GL-5 75W-90**

Mixture ingredients affecting the classification: Reaction product of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide, and amines, C12-C14-alkyl (branched), reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses: It is intended to lubricate manual gear boxes and other gears of vehicles operating in difficult conditions i.e. high speed and low torque or low speed and high torque

Uses advised against: other uses not recommended

1.3. Details of the supplier of the safety data sheet

Supplier: **ORLEN OIL Sp. z o.o.**

Address: 31-323 Kraków, ul. Opolska 114

Telephone No/Fax No: +48 12 66 555 00 / +48 12 66 555 01

E-Mail: msds@orlenoil.pl

(current safety data sheets are available on web site: www.orlenoil.pl)

1.4. Emergency telephone number

+ 48 24 201 03 67 or +48 13 43 84 415 (available from Monday till Friday during office hours: 7 am – 3 pm)

In case of emergency call 112 (Emergency number), 998 (Fire Brigade), 999 (Ambulance Service)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification	According to Regulation (EC) No 1272/2008 (CLP)
Hazard	
for physical-chemical properties:	Not classified as hazardous
for health hazards:	Skin Sens. 1, H317
for environmental hazards:	Aquatic Chronic 2, H411

2.2. Label elements



Hazard pictogram(s):

Signal word(s): **Warning**

Hazard statement(s):

H317 - May cause an allergic skin reaction.

H411- Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 2 of 10

Precautionary statement(s):

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 – IF ON SKIN: Wash with plenty of soap and water.

P273 - Avoid release to the environment.

P501 Dispose of contents/container to a licensed waste disposal company.

Additional information on the label:

It contains: Reaction product of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide, and amines, C12-C14-alkyl (branched), reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives.

2.3. Other hazards

The product does not meet the PBT and vPvB criteria set out in Annex XIII to the REACH Regulation. Flammable product of high flash point.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances – not applicable

3.2. Mixtures: mixture of mineral and synthetic base oils and enriching additives

Hazardous ingredients and its concentrations in the mixture:

Substance name	REACH registration number	CAS No/ EC No	% wt.	Classification according to EC Regulation No.1272/2008 (CLP)
Reaction product of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide, and amines, C12-C14-alkyl (branched) 01-2119493620-38	931-384-6	0,65 – 1,62	-	Acute Tox. 4; H302 Aquatic Chronic 2; H411 *Eye Dam. 1; H318 Skin Sens. 1; H317
(Z)-octadec-9-enylamine	204-015-5	0,32 - 0,65	-	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (M=10) Asp.Tox.1; H304 Eye Dam. 1; H318 Skin Corr. 1B; H314 STOT RE2; H373 STOT SE3; H335
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives. 01-2119971727-23	939-460-0	0,06- 0,19	-	Aquatic Chronic 3; H412 Eye Dam. 1; H318 Skin Corr 2; H315 Skin Sens. 1B; H317

*Concentration limits

Eye Dam. 1: 50% < C ≤ 100

Description of the H phrases is given in Section 16. Base oils applied in the mixture **are not classified as carcinogenic**. DMSO extract content (according to IP 346) <3%. Based on viscosity it does not pose hazard by aspiration.

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 3 of 10

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:

Due to the low content of volatile compounds the oil at ambient temperature does not pose inhalation hazard. The risk of inhalation exists in case of product mist formation or as a result of heating. Remove the victim (move/carry) from the exposure area to fresh air and keep warm and quiet. Place an unconscious person in the recovery position, loosen tight parts of clothes; control and maintain patency of the airways. Give oxygen in the case of breathing disorders; if not breathing, use artificial ventilation. In the case of loss of consciousness, respiratory disorders or persisting symptoms obtain medical aid immediately.

Contact with skin:

Immediately remove contaminated/soaked clothes and shoes. Thoroughly wash contaminated skin with soapy water or mild detergent, and then rinse with water. Consult a doctor if irritation symptoms appear and persist.

NOTE: Take off contaminated/soaked clothes and remove it to a safe place, far from heat and ignition sources.

Contact with eyes:

Flush contaminated eyes with running water, remove contact lenses (if present) and continue flushing for approx. 15 minutes. When flushing, keep the eyelids wide open and keep moving the eyeballs. When symptoms appear and persist, consult a doctor.

NOTE: Do not use too strong stream of water which may damage the cornea.

Ingestion:

DO NOT INDUCE VOMITING – increased risk of aspiration. In the case when spontaneous vomiting occurs, keep the victim leaning forward, with her/his face directed to the ground. Ensure medical assistance.

4.2. Most important symptoms and effects, both acute and delayed

The product has negative effects on the central nervous system. Upon inhalation, its narcotic effect in the concentration of 8 mg/l in air causes nausea to narcosis, while concentrations of 40 mg/l may be fatal after 5 to 10 minute inhalation. Repeated exposures may cause chronic neurologic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Do not induce vomiting and do not administer anything orally to an unconscious person. Show safety data sheet or the label / packaging to the medical personnel providing assistance. A person providing first aid in the area where vapour/fog concentration is unknown should be equipped with the appropriate respiratory protection.

Indications for a doctor: symptomatic treatment.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media: carbon dioxide, dry powder, foam; water spray.

Unsuitable Extinguishing Media: water jet.

5.2. Special hazards arising from the substance or mixture

Flammable product. In the fire environment smokes containing carbon oxides and other unidentified thermal decomposition products of higher hydrocarbons are formed. Avoid breathing products being released in the fire environment.

5.3. Advice for firefighters

Proceed in accordance with procedures applicable for extinguishing chemical fire. In the case of fire involving great amounts of the product, remove all bystanders not participating in action; call emergency brigades and the Fire Brigade.

Cool the containers exposed to fire or high temperature with water spray from a safe distance, if possible and remove them from the endangered area.

Prevent the wastewater after fire extinguishing from penetrating sewage and water tanks. Remove wastewater and residue after firefighting in accordance with valid regulations.

People participating in the fire-extinguishing action should be properly trained, equipped with a full protective clothing and a self-containing breathing apparatus.

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 4 of 10

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use individual protection measures – see section 8 of the Safety Data Sheet.

Limit the access of bystanders to the endangered area until proper cleaning operations are finished. Ensure that breakdown and its results are eliminated by a properly trained staff only.

Avoid eyes, skin and clothing contamination. NOTE: Spilled oils can make surfaces slippery.

6.2. Environmental precautions

If possible and safe, stop or limit product release. Limit large spillage by embanking the area. Prevent from entering sewers, rivers or other bodies of water and soil. Notify respective authorities (Occupational Safety and Health Administration, emergency brigades, Environment Protection Authority and Local Administration).

6.3. Methods and material for containment and cleaning up

Cover up small spillage with non-flammable, neutral absorbent material (sand, soil, diatomic earth, vermiculite) and collect in an appropriate, closed, labelled waste bin. Clean the contaminated area with water with detergent, and then rinse with water. Pump off large amounts of liquid. Dispose of according to the applicable regulations. If necessary, obtain help from specialist companies dealing with waste transport and utilisation in order to remove the product/absorbent material contaminated with the product. Use the services of professional waste transport/ utilization companies.

6.4. Reference to other sections

Refer to Sections 8 and 13 of the safety data sheet.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Provide effective ventilation. Avoid contact with the eyes, skin and clothes. Keep unused containers tightly closed. Essential hygiene rules should be observed: do not eat, drink or smoke during work, wash hands with soapy water after work/after break in work. Do not use contaminated clothing; Immediately remove contaminated clothing and wash before reuse. NOTE: Take off contaminated/soaked clothes and remove it to a safe place, far from heat and ignition sources. Use individual protection measures in accordance with the information contained in section 8 of the Safety Data Sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly sealed and properly labelled containers, in a cool, well ventilated place with a non-absorbing ground. The product may be stored in storage tanks in accordance with applicable regulations. Store far from heat sources, protect from direct sunlight. Protect against contamination and water accumulation. Keep away from strong oxidisers. Prevent the product from penetrating ground and water.

7.3. Specific end use(s)

None.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Control parameters

Highly refined mineral oils – inhaled fraction: TLV-TWA: 5 mg/m³, TLV-STEL: - mg/m³, TLV-C: –

Directive of the Minister of Work and Social Policy dated June 6th, 2014 on the maximum occupational levels of factors hazardous to health at the workplace (Dz.U. 2014, item 817)

Unspecified base oil:

DNEL_{worker} (oral, chronic toxicity)

5.4 mg/m³/8h (aerosol)

DNEL_{consumer} (oral, chronic toxicity)

1.2 mg/m³/24h (aerosol)

PNEC_{water, sediment, soil, wastewater treatment plant, mammals}

Not applicable (a substance does not pose a danger to environment)

PNEC (oral, mammals)

9.33 mg/kg of food

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 5 of 10

8.2. Exposure controls

Recommended methods of exposure assessment in the air:

- PN-Z-04008-7:2002 – "Air purity protection -- Sampling methods -- Principles of air sampling in work place and interpretation of results"
- PN-Z-04108-6:2006 „Air purity protection -- Determination of mineral oil (liquid phase aerosol) in work places by absorption spectrometry method in ultra-violet ”.
- PN-Z-04108-5:2006 „Air purity protection -- Tests for content of oils -- Determination of mineral oil (liquid phase of aerosol) in work places by absorption spectrometry method in infra-red"

Appropriate engineering controls:

General ventilation and/or local fume hood in order to keep concentration of the product below the exposure limits.

Eye/face protection:

Use tight safety glasses (goggles) in the case of prolonged exposure or when splashing the liquid to the eye is possible. It is recommended to equip the workplace with a water shower for eyes flushing.

Skin protection:

Wear impermeable, oil resistant gloves (e.g. perbutane, viton, butyl rubber). In case of short term contact use protective gloves of effectiveness level 2 and breakthrough time > 30 min. In case of prolonged contact use protective gloves of effectiveness level 6 and breakthrough time > 480 min. It is recommended to use protective clothes and oil-resistant, anti-slippery shoes.

Respiratory protection:

Not required under normal conditions of use. In the case of exceeding the acceptable limits or inadequate ventilation use the approved respirator equipped with a suitable filter or filter-absorber.

Thermal hazards:

Not applicable.

Environmental exposure controls:

Consider using precautionary measures in order to protect the area around storage tanks.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

a) Appearance	: Liquid; colour: light yellow to amber
b) Odour	: typical for oil
c) Odour threshold	: No data available
d) pH	: Not applicable
e) Melting point/freezing point	: ≤-45°C
f) Initial boiling point and boiling range	: no data available
g) Flash point	: > 165°C
h) Evaporation rate	: no data available
i) Flammability (solid, gas)	: Not applicable
j) Upper/lower flammability or explosive limits	: no data available
k) Vapour pressure	: no data available
l) Vapour density	: no data available
m) Relative density	: approx.0,88 g/cm ³
n) Solubility(ies)	: Insoluble in water. Soluble in hydrocarbon solvents.
o) Partition coefficient: n-octanol/water	: no data available
p) Auto-ignition temperature	: no data available
q) Decomposition temperature	: no data available
r) Viscosity	: 13,5-24 mm ² /s at 100°C, above 110 mm ² /s (40 °C)
s) Explosive properties	: no data available
t) Oxidising properties	: no data available

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 6 of 10

9.2. Other information

None

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Product is not reactive.

10.2. Chemical stability

Product is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3. Possibility of hazardous reactions

Not known.

10.4. Conditions to avoid

High temperature, open flame and other ignition sources.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Not known.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity:

Data for base oil:

LD50: >5000 mg/kg (oral, rat)

LC50: > 5.53 mg/l (inhalation, rat)

LD50: >5000 mg/kg (skin, rabbit)

Skin corrosion/irritation:

Prolonged contact with a product may cause skin irritation.

Serious eye damage/irritation:

Classification criteria have not been met based on the available data.

Respiratory or skin sensitisation:

May produce allergic reaction to skin.

Germ cell mutagenicity:

Not applicable.

Carcinogenicity:

Classification criteria have not been met based on the available data. Based on L Note the substances included in the mixture are not classified as carcinogenic (DMSO extract content (according to IP 346) < 3%).

Reproductive toxicity:

Not applicable.

STOT-single exposure:

Accidental ingestion may cause gastric disturbances (nausea, vomiting, stomach pain);

STOT-repeated exposure:

Repetitive or prolonged exposure may cause drying, cracking or chronic inflammation of the skin. May cause irritation to respiratory tract when present in form of oil mist or vapors at high temperatures (above 60° C).

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic organisms with long lasting effects.

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 7 of 10

12.2. Persistence and degradability

Limited level of biodegradability.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The product may be hazardous to the environment in case of unsuitable use or in emergency situations – product penetrates into soil and causes contamination of ground water.

12.5. Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB criteria set out in Annex XIII to the REACH Regulation.

12.6. Other adverse effects

The product is insoluble in water and spreads over its surface forming a light film.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste code: **13 02 05*** mineral-based non-chlorinated engine gear and lubricating oils.

NOTE: Since waste code is assigned based on the source of origin, the end user should define the obtained wastes and assign a proper code, taking into consideration specific conditions of use, in accordance with applicable regulations.

Soaked clothes, papers or other organic materials should be collected and utilised in an controlled way.

Do not dispose to sewer. Avoid contamination of surface and ground waters. Consider reuse. Waste product should be recovered or utilised at professional, approved furnaces or waste recycling/neutralization facilities, in accordance with applicable regulations.

Recovery / recycling / utilisation of package wastes should be performed according to the applicable regulations.

NOTE: Only completely emptied and cleaned packages may be returned for recycling. Use services of authorised companies.

The Act of 14 December 2012 on wastes (Dz.U. of year 2013, item 21)

The Act of 13th June 2013 on the catalogue on package and package waste management (Journal of Laws of 2013 item 888). Regulation of the Minister of Environmental Protection of 9th December of waste (Journal of Laws 2014 item 1923).

SECTION 14. TRANSPORT INFORMATION



The product is subjected to transport regulations on hazardous goods included in ADR (road transport), RID (rail transport), IMDG (marine transport) and ICAO/IATA (air transport).

14.1. UN number

UN 3082

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (contains: (Z) -octadec-9-phenylamine, amine salt of phosphoric acid esters)

14.3. Transport hazard class(es)

9

90

No 9

III

14.4. Packing group

14.5. Environmental hazards

Substance hazardous to environment

14.6. Special precautions for user

None

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Revision: 26.06.2017

Version: 5.0 CLP

Page 8 of 10

Made on: 23.05.2011

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Act of 25 February 2011 on chemicals and their mixtures (Journal of Laws of 2011 No. 63 item 322)
Regulation of the Minister of Health of 20 April 2012 on labelling packaging of dangerous substances and dangerous mixtures and some mixtures (Journal of Laws 12, item 445)
Regulation (EC) No. 1907/2006 of the European Parliament of 18 December 2006 on registration, evaluation and authorisation of chemicals (REACH) and establishing the European Chemicals Agency, amending Directive No.1999/45/WE and repealing regulation of the Council (EEC) No. 793/93 and regulation of the Commission (EC) No. 1488/94, as well as the Council Directive No. 76/769/EEC and Commission Directive No. 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (correction Journal of Laws of 29 May 2007 as amended)
Regulation of the Commission (EC) No. 453/2010 of 20 May 2010 amending regulation (EC) No. 1907/2006 of the European Parliament and the Council of 18 December 2006 on registration, evaluation and authorisation of chemicals (REACH) (Journal of Laws L 133 of 31 May 2010)
Regulation of the European Parliament and the Council (EC) No. 1272/2008 of 16 December 2008 on classification, labelling and packing substances and mixtures, amending and repealing directives 67/548/EEC and 1999/45/EC and amending regulation (EC) No. 1907/2006 (Journal of Laws No. 353 of 31 December 2008 as amended)
Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of factors harmful to life in the working environment (Journal of Laws of 2011, No. 33, item 166)
Regulation of the Minister of Economy of 21 December 2005 on essential requirements for personal protection (Journal of Laws of 2005 No. 259, item 2173)
Regulation of the Minister of Health and Social Care of 30 May 1996 on medical examination of employees, scope of preventive health care and medical certificates issued for purposes stipulated in the Labour Code (Journal of Laws of 1996, No. 69, item 332; of 1997 No. 60, item 375; of 1998 No. 159, item 1057; of 2001 No. 37, item 451; No. 128, item 1405)
Regulation of the Minister of Health and Social Policy of 26 September 1997 on general occupational health and safety regulations (consolidated text, Journal of Laws of 2003 No. 169, item 1650; of 2007 No. 49, item 330; of 2008 No. 108, item 690)
Regulation of the Minister of Health of 30 December 2004 on occupational health and safety related to the presence of chemical agents in the workplace (Journal of Laws of 2005 No. 11, item 86; of 2008 No. 203, item 1275)
Act of 24 August 1991 on fire protection (consolidated text, appendix to the Journal of Laws of 2002 No. 147 item 1229; of 2003 No. 52, item 452; of 2004 No. 96, item 959; of 2005 No. 100, item 835 and 836; of 2006 No. 191, item 1410; of 2007 No. 89, item 590; of 2008 No. 163, item 1015; of 2009 No. 11, item 59)
European Agreement concerning the international carriage of dangerous goods by road (ADR), concluded in Geneva on 30 September 1957, as amended, effective as of the date of entry into force for the Polish Republic, proclaimed in the right way (Dz. U. of 2011. No 110, item 641);
Act of 19 August 2011 on the carriage of dangerous goods (Dz. U. of 2011, No 227, item 1367).

15.2. Chemical safety assessment

Chemical safety assessment is not required for a mixture.

SECTION 16. OTHER INFORMATION

Changes made in the safety data sheet during revision:

Changes in sections: 16

Legend to abbreviations and acronyms used in the safety data sheet:

TLV-TWA Threshold Limit Value
TLV-STEL Threshold Limit Value, Short Term Exposure Limit
TLV-C Ceiling exposure limit

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 9 of 10

vPvB	Very persistent and very bioaccumulative (substance)
PBT	Persistent, bioaccumulative and toxic (substance)
PNEC	Predicted No Effect Concentration
DNEL	Derived No Effect Levels
LD ₅₀	Lethal Dose 50%, dose required to kill half the members of a tested population after a specified test duration
LC ₅₀	Lethal Concentration, 50 dose required to kill half the members of a tested population after a specified test duration
EC _x	X % maximal effective concentration, concentration which induces a response halfway between the baseline and maximum after some specified exposure time
LOEC	Lowest Observed Effect Concentration
NOEL	No Observed Effect Concentration
RID	The International Rule for Transport of Dangerous Substances by Railway
ADR	The European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	The International Maritime Dangerous Goods
IATA	The International Air Transport Association
UVCB	Unknown or Variable composition, Complex reaction or Biological materials

Literature references and sources for data:

Regulations/legislations mentioned in sections 2 – 15 of safety data sheet.
Chemical safety report for mixture ingredients.

List of relevant R phrases, hazard statements, safety phrases and/or precautionary statements, which are not written out in full under Sections 2 to 15:

The list of applicable H-phrases

H302 - Harmful if swallowed.
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life.
H410 - Very toxic to aquatic life with long lasting effects.
H411 - Toxic to aquatic life with long lasting effects.
H412 - Harmful to aquatic life with long lasting effects.

The list of applicable CLP classification phrases

Aquatic Acute 1 - Hazardous to aquatic environment, cat. 1 (acute)
Aquatic Chronic 1 - Hazardous to aquatic environment, cat. 1 (chronic)
Aquatic Chronic 2 - Hazardous to aquatic environment, cat. 2 (chronic)
Aquatic Chronic 3 - Hazardous to aquatic environment, cat. 3 (chronic)
Acute Tox. 4 - Acute, Cat. 4
Eye Dam. 1 - Serious eye damage / eye irritation, cat. 1
Skin Irrit. 2 - corrosion / irritation, cat. 2
Skin Corr. 1B - corrosion / irritation, cat. 1B
Skin Sens. 1 - Skin sensitization, Cat. 1
Skin Sens. 1B - Skin sensitization, cat. 1B
Asp.Tox.1 - Aspiration hazard, Cat. 1
STOT RE2- organ toxicity Target (repeated exposure) cat.2
STOT SE3- organ toxicity Target (single exposure), category 3

Advice on any training appropriate for workers to ensure protection of human health and the environment:

SAFETY DATA SHEET

In accordance with Regulation (EU) No 1907/2006 with amendments (2015/830)

HIPOL SEMISYNTHETIC GL-5 75W-90

Made on: 23.05.2011

Revision: 26.06.2017

Version: 5.0 CLP

Page 10 of 10

Workers that use the product should be trained and informed about health hazards, personal protection, accident preventive actions, rescue actions, etc.

MSDS is not a quality certificate for the product. Information provided herein serves only as guidelines for safe handling during transport, distribution, use and storage. Persons handling the product should be informed about risks and precautionary measures. This information applies only to specific material designated and may not be suitable for such material used in combination with any other materials or in any other manner not described in this document.

The user is obliged to follow all applicable standards and regulations and is also responsible for inappropriate use of information contained in this sheet or inappropriate use of the product. In case of special use to ensure safe work, exposure should be re-estimated, appropriate procedure and training programs should be developed.

Additional information: Classification was made on basis of data for hazardous ingredients content by calculation method according to the guidelines of Regulation 1272/2008 / EC (CLP) with amendments.
