



PLATINUM GEAR LX 85W-140

QUALITY CLASS: API: GL-5
VISCOSITY GRADE: SAE: 85W-140

GENERAL FEATURES:

Platinum Gear LX 85W-140 is a high-performance gear oil designed for trucks, construction and agricultural machines. Due to the good oxidation resistance and carrying high loaded capacity provides protection of transmission elements during the entire operation.

Guarantees:

- stability of the lubricating properties during operation
- High load carrying capacity,
- Excellent lubricity and anti-wear properties.

APPLICATION:

Platinum Gear LX 85W-140 is intended for use primarily in final drives and rear axles.

STANDARDS, APPROVALS. SPECIFICATION:

ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 17B, 19B, 21A, 02A, 02B, 17A

Scania STO 1:0

Volvo 1273.10

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Units	Typical values
SAE Viscosity grade	-	85W-140
Kinematic viscosity at 100°C	mm ² /s	27,5
Viscosity index	-	95
Solidification point	°C	-23
Flash-point	°C	230

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

